



Universal catalytic converter gasoline 2.5-5.0 RFC



Product codes:

Reference: KS21

EAN13: 5904347512361



Product features:

Inlet pipe diameter: 63,5 mm
Catalyst application: Gasoline
Cartridge type: Standard
Cartridge material: Metal - type S
Producer: RFC
Total length: 310 mm
Catalyst diameter: 120 mm
Engine capacity: 2.5-5.0L
Shape of the catalyst: round

Product attributes:

euro standard: Euro 2, Euro 4, Euro 5
Capacity (cpsi): 400, 500

Product description:

S409 stainless steel sports catalytic converter with a metal S-type insert featuring 3 cores for increased performance and durability. Compatible with gasoline, diesel, and LPG engines. When installed in parallel, they support an engine displacement 50% greater than the rated capacity.

- Continuous temperature resistance of 1100 °C
- Short-term temperature resistance of 1150 °C

Depending on the selected configuration, the catalytic converter meets the requirements of the European directive:

- EURO 2 Directive 94/12/EC, 96/69/EC for passenger cars, effective since 1996.
- EURO 3 Directive 98/69/EC [12] for all vehicles, effective since 2000.
- EURO 4 Directive 98/69/EC, 2002/80/EC for all vehicles, effective since 2005.
- EURO 5 Directive 2007/715/EC[13] for light passenger and commercial vehicles. Effective as of 2009.

Manufacturer's warranty: 12 months or 50,000 km.