

Universal catalytic converter gasoline 0.7-2.5 RFC



Product codes:

Reference: KS11

EAN13: 5904347512361



Product features:

Inlet pipe diameter: 63,5 mm Catalyst application: Gasoline

Cartridge type: Standard

Cartridge material: Metal - type S

Producer: RFC

Total length: 310 mm

Catalyst diameter: 112 mm Engine capacity: 0.7-2.5L Shape of the catalyst: round

Product attributes:

euro standard: Euro 2, Euro 4, Euro 5, Euro 6

Capacity (cpsi): 400, 500, 600

Product description:

Universal S409 stainless steel catalytic converter with S-type metal cartridge with 3 cores for increased performance and durability. Compatible with gasoline engines and LPG systems. Mounted in parallel, supports engine capacities up to 5 liters.

- Permanent temperature resistance of 950 °C
- Instantaneous temperature resistance of 1100 °C

The catalytic converter, depending on the selected configuration, meets the requirements of the European directive:

- EURO 2 Directive 94/12/EC, 96/69/EC for passenger cars, effective since 1996.
- EURO 4 Directive 98/69/EC, 2002/80/EC for all vehicles, effective from 2005.
- EURO 5 Directive 2007/715/EC[13] for light passenger and company cars. Effective since 2009.
- EURO 6 Commission Regulation (EU) No. 459/2012, effective from 2014.

Manufacturer's warranty: 12 months or 50,000 km.