



---

# Regenerated Catalytic Converter for Mercedes W203/S203 C180 Kompressor, C200 Kompressor, C200 CGI, C230 Kompressor, C230



**Product codes:**

Reference: REG/A2711401409



---

EAN13: -

**Product features:**

Cartridge material: Metal  
Producer: OE  
Engine capacity: 1.8-2.5  
Year of production: 2002-2008 EURO 4  
Horsepower: 143, 163, 170, 192, 204 HP  
OE number: A2711401409 KT0212, A2711400209  
KT0200, A2711403009 KT0267, A2711402309  
KT0201, A2711402109 KT0212, A2711402709  
KT0242  
Product type: Regenerated  
Engine code: M271.946, M271.940, M271.942,  
M271.948, M272.920, M272.929  
Warranty: 12 months

**Product attributes:**

euro standard: Euro 4  
Deposit: With the return of the old part, Without  
returning the old part

**Product description:**

**NO RETURN OF OLD PART REQUIRED**

Purchase without returning the old part—we ship the item immediately. You can return your old catalytic converter within 30 days of the purchase date and receive a refund of your deposit. The returned part must be complete, original, marked with an OE number, and free of mechanical damage or signs of tampering.

**WITH RETURN OF THE OLD PART**

Purchase with return of the old part – we ship the product after receiving the old catalytic converter. The part must be complete, original, marked with an OE number, and must not have any mechanical damage or signs of tampering.

**If you're not sure whether the catalytic converter fits your car, contact us via [contact form](#) and provide your VIN number, which will speed up the verification process.**

**Catalytic converter regeneration involves replacing the worn-out insert with a new metal one, restoring the system to full efficiency and meeting EURO 4 emissions standards. The regeneration process uses high-quality metal inserts with a flow rate of 500 cpsi, matching the original specifications. Thanks to these inserts, no errors occur in the engine control unit. In rare cases, however, it may be necessary to manually clear the error using computer diagnostics, which is a standard procedure following the replacement of exhaust system components.**