

QCAT universal catalyst cartridge



Product codes:

Reference: 1051345

EAN13: -



Product features:

Catalyst application: Gasoline Cartridge type: Standard

Cartridge material: Metal - type S

Producer: OCAT

Product attributes:

euro standard: Euro 4, Euro 5, Euro 6

Inlet diameter: 100 mm, 105 mm, 110 mm, 125 mm,

130 mm, 150 mm Insert length: 100 mm Capacity (cpsi): 400

Product description:

Universal S-type metal catalytic converter cartridge with 3 cores for increased performance and durability. Compatible with gasoline engines and LPG systems.

- Permanent temperature resistance 950 °C
- Temperature resistance 1100 °C

Catalytic converter meets the requirements of the European Directive:

• Euro 5 Directive 2007/715/EC[13] for light passenger and company cars. Effective from 2009.

Manufacturer's warranty: 12 months or 50,000 km.

The catalytic converter cartridge is selected based on the emission standard it is supposed to meet and its dimensions. Unfortunately, no catalog gives the dimensions of the cartridge, because theoretically it is a non-interchangeable part, so in order to properly select the cartridge you need to measure the diameter and length of the catalytic converter housing. Then subtract the thickness of the wall of the catalytic converter housing, since the cartridge is located inside the housing. For example, if the catalytic converter housing has a diameter of 110 mm, a cartridge with a diameter of 105 mm would be suitable.