



Sport catalytic converter 2.5-5.0 RFC ceramic coating



Product codes:

Reference: KS21

EAN13: -



Product features:

Inlet pipe diameter: 63,5 mm
Capacity (cpsi): 200 cpsi
Cartridge type: Sport
Cartridge material: Metal - type S
Producer: RFC
Total length: 230 mm
Catalyst diameter: 120 mm
Engine capacity: 2.5-5.0L
Shape of the catalyst: round
Ceramic coating: Yes

Product attributes:

euro standard: Euro 4, Euro 5
Capacity (cpsi): 200

Product description:

S409 stainless steel sport catalytic converter with S-type metal cartridge with 3 cores for increased performance and durability. Compatible with gasoline engines, diesel engines and LPG systems. When fitted in parallel, they can handle an engine capacity 50 per cent greater than the stated capacity. The cone on one side has been shortened, allowing the catalytic converter to be installed in cars with limited space. The ceramic coating reduces heat transfer from the exhaust system considerably, which helps to keep the exhaust gas temperature higher inside the system. This allows the exhaust gas to travel faster, which can improve gas flow and engine performance. The higher temperature inside the catalytic converter results in higher performance in exhaust gas cleaning - the ceramic coating makes it reach its ideal temperature faster and releases less heat to the outside.

- Permanent temperature resistance **1100 °C**
- Temperature resistance **1150 °C**

The catalytic converter meets the requirements of the European directive:

- EURO 4 Directive 98/69/EC, 2002/80/EC for all vehicles, in force since 2005.
- Euro 5 Directive 2007/715/EC[13] for light passenger and company cars. Effective from 2009.

Manufacturer's warranty: 12 months or 50,000 km.